

# HC

Perfect for residential projects, the indoor HC controller provides smart water savings and remote irrigation management capabilities.

## KEY BENEFITS

- Number of stations:
  - 6 or 12 (fixed indoor)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 24-hour maximum station run time provides flexibility for low-flow zones
- 2 sensor inputs available for use with any Clik sensors and HC Flow Meter
- Station outputs can also be used to activate a pump start relay or master valve
- Wi-Fi enabled for quick connection to Hydrawise software
- 7 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts (12-station model only)


## OPERATING SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 2 years



**HC**  
(plastic indoor)  
Height: 15.2 cm  
Width: 17.8 cm  
Depth: 3.3 cm

Compatible with:



**HC Flow Meter**  
Page 147



**Rain-Clik Sensor**  
Page 144



**Soil-Clik Sensor**  
Page 151



**Smart WaterMark**  
Recognised as a responsible water-saving tool

HC	
Model	Description
HC-600i	Fixed 6-station, plastic indoor wall mount, 120 VAC transformer
HC-601i-E	Fixed 6-station, plastic indoor wall mount, 230 VAC transformer with European connections
HC-601i-A	Fixed 6-station, plastic indoor wall mount, 230 VAC transformer with Australian connections
HC-1200i	Fixed 12-station, plastic indoor wall mount, 120 VAC transformer
HC-1201i-E	Fixed 12-station, plastic indoor wall mount, 230 VAC transformer with European connections
HC-1201i-A	Fixed 12-station, plastic indoor wall mount, 230 VAC transformer with Australian connections